









TS70145 Track Spotlight

Input Voltage AC220-240V, Multivoltage
 Light Power 18W
 Luminous flux ~1755lm
 Light Source CREE
 CCT 3000K, 4000K
 CRI 80 as standard, CRI90, 95, 97
 Beam Angle Reflector 15°, 30°, 45°
 Driver, Khun, Xz, Philips other options available
 Dimmable 0-10V, Triac, Dali as an option



TS85160 Track Spotlight

Input Voltage AC220-240V, Multivoltage
 Light Power 25W
 Luminous flux ~2410lm
 Light Source CREE
 CCT 3000K, 4000K
 CRI 80 as standard, CRI90, 95, 97
 Beam Angle Reflector 15°, 30°, 45°
 Driver, Khun, Xz, Philips other options available
 Dimmable 0-10V, Triac, Dali as an option




TS95170 Track Spotlight

Input Voltage AC220-240V, Multivoltage
 Light Power 33W
 Luminous flux ~3490lm
 Light Source CREE
 CCT 3000K, 4000K
 CRI 80 as standard, CRI90, 95, 97
 Beam Angle Reflector 15°, 30°, 45°
 Driver, Khun, Xz, Philips other options available
 Dimmable 0-10V, Triac, Dali as an option





TS85104 Track Spotlight

Input Voltage AC220-240V, Multivoltage
 Light Power 18W
 Luminous flux ~1755lm
 Light Source CREE
 CCT 3000K, 4000K
 CRI 80 as standard, CRI90, 95, 97
 Beam Angle Reflector 12°, 24°, 45°, 55°
 Driver, Khun, Xz, Philips other options available
 Dimmable 0-10V, Triac, Dali as an option



TS95112 Track Spotlight

Input Voltage AC220-240V, Multivoltage
 Light Power 25W
 Luminous flux ~2610lm
 Light Source CREE
 CCT 3000K, 4000K
 CRI 80 as standard, CRI90, 95, 97
 Beam Angle Reflector 15°, 30°, 40°, 55°
 Driver, Khun, Xz, Philips other options available
 Dimmable 0-10V, Triac, Dali as an option



TS106123 Track Spotlight

Input Voltage AC220-240V, Multivoltage
 Light Power 33W
 Luminous flux ~3490lm
 Light Source CREE
 CCT 3000K, 4000K
 CRI 80 as standard, CRI90, 95, 97
 Beam Angle Reflector 12°, 30°, 45°, 60°
 Driver, Khun, Xz, Philips other options available
 Dimmable 0-10V, Triac, Dali as an option