I.P. (Ingress Protection) Ratings Guide


Please note that these are basic regulations regarding bathroom lighting. Other precautions may be required. Your electrician and contractor will have further details. Please before installing consult your country regulations.

Zone 0 - *Inside the bath or shower*. Any fittings used here must be SELV(Separated Extra Low Voltage – max. 12Volts) and have a minimum rating of IPX7(IP67) (protected against immersion in water – total immersion proof)

Zone 1 - *Above the bath or shower to a height of 2.25m* A minimum rating of IPX4(IP44) is required. In this zone, if there is likelihood of water jets being used for cleaning purposes, a minimum of IPX5 is required. Also, subject to IP rating, SELV or 240V luminaires may be used in this zone; if the fitting is 240 volts, a 30mA residual current device (RCD) must also be used to protect the circuit in this zone.

Zone 2 - The area stretching to 0.6m outside the bath or shower and above the bath or shower to 2.25m An IP rating of at least IPX4(IP44) is required. In this zone, if there is likelihood of water jets being used for cleaning purposes, a minimum of IPX5 is required. Also, subject to IP rating, SELV or 240V luminaires may be used in this zone. In addition, it is a good practice to also consider the area around a wash basin (within a 60cm radius of any tap) as Zone 2.

Outside the zones, zone 3 - anywhere outside zones 0, 1 and 2. Where water jets are not to be used for cleaning purposes, the general rules of BS7671 apply. Here, there are no requirement for any lighting to be IP rated against water or solids ingression.





IP54 AND IP65 LED DOWNLIGHTS

nelux architectural lighting

Ø80mm

Ø70mm

Optional rings OO OO OO

Color palette







SL8065 IP54 SPOT LIGHT

Input Voltage AC220-240V, Multivoltage Light Power 5W, 10W Luminous flux ~425Im, ~850Im Light Source Epistar cob CCT 2700K, 3000K, 4000K

CRI >80, CRI 90 and CRI 97 as an option Beam Angle 24°, 38°, 60°

Driver, Khun, Xz other options available Dimmable 0-10V, Triac, Dali as an option

Optional Reflector Silver, Gold, Black, White, Green, Blue

SL11076


SL8065

65mm


Input Voltage AC220-240V, Multivoltage Light Power 10W, 15W Luminous flux ~850lm, ~1275lm Light Source Epistar cob CCT 2700K, 3000K, 4000K CRI >80, CRI 90 and CRI 97 as an option Beam Angle 24'', 38', 60° Driver, Khun, Xz other options available Dimmable 0-10V, Triac, Dali as an option Optional Reflector Silver, Gold, Black, White, Green, Blue

SL8065S

Input Voltage AC220-240V, Multivoltage Light Power 5W, 10W Luminous flux ~425Im, ~850Im Light Source Epistar cob CCT 2700K, 3000K, 4000K CRI >80, CRI 90 and CRI 97 as an option Beam Angle 24°, 38°, 60° Driver, Khun, Xz other options available Dimmable 0-10V, Triac, Dali as an option Optional Reflector Silver, Gold, Black, White, Green, Blue











SL10576

Input Voltage AC220-240V, Multivoltage Light Power 10W, 15W Luminous flux ~850lm, ~1275lm Light Source Epistar cob CCT 2700K, 3000K, 4000K CRI >80, CRI 90 and CRI 97 as an option Beam Angle 24'', 38'', 60'' Driver, Khun, Xz other options available Dimmable 0-10V, Triac , Dali as an option Optional Reflector Silver, Gold, Black, White, Green, Blue


FIRENZE IP54 SERIES

IP54 AND IP65 LED DOWNLIGHTS

nelux architectural lighting







SL7853 IP65 SPOT LIGHT

Input Voltage AC220-240V, Multivoltage Light Power 8W Luminous flux ~710lm Light Source Epistar cob CCT 2700K, 3000K, 4000K CRI >80, CRI 90 and CRI 97 as an option Beam Angle 45° External Driver, Khun, Xz other options available Dimmable 0-10V, Triac , Dali as an option Color Silver, Black, White

SL9852 IP65 SPOT LIGHT

Input Voltage AC220-240V, Multivoltage Light Power 8W Luminous flux ~710lm Light Source Epistar cob CCT 2700K, 3000K, 4000K CRI >80, CRI 90 and CRI 97 as an option Beam Angle 45° External Driver, Khun, Xz other options available Dimmable 0-10V, Triac, Dali as an option Color Silver, Black, White





IP65 and IP54 led products waterproof are ideal for kitchen, bathroom, terraces, spa, wellness center, beachfront properties.

